



**2015** LOAD AND INFLATION TABLES

TABLE OF CONTENTS | **Load & Inflation Tables**

**Medium Commercial Truck Radials** ..... 104 - 108

*Radial Ply Metric Tires on 15° Drop Center Rims*..... 104 - 106

*Radial Ply Metric Wide Base Tires as Singles* ..... 105

*Radial Ply Tires on 15° Drop Center Rims*..... 107

*Radial Ply Tires on Flat Base Rims* ..... 108

**Commercial Light Truck Radials** ..... 109 - 112

*Radial Ply Metric Tires on 5° Drop Center Rims*..... 109 - 110

*Radial Ply Tires on 5° Drop Center Rims*..... 111

*Diagonal Bias Ply Tires on 5° Drop Center Rims* ..... 111

*Radial Ply Tires on Flat Base Rims* ..... 112

# Medium Commercial Truck Radials

Radial Ply METRIC Tires for Trucks, Buses & Trailers Used in Normal Highway Service

## TIRES MOUNTED ON 15° DROP CENTER RIMS

| TIRE SIZE DESIGNATION                                 | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load) |      |      |                               |      |      |                               |                               |      |                               |      |                               |                        |
|---|--------|--|------|------|-------------------------------|------|------|-------------------------------|-------------------------------|------|-------------------------------|------|-------------------------------|------------------------|
|   |        | kPa  | 480  | 520  | 550                           | 590  | 620  | 660                           | 690                           | 720  | 760                           | 790  | 830                           | 860                    |
|   |        | psi  | 70   | 75   | 80                            | 85   | 90   | 95                            | 100                           | 105  | 110                           | 115  | 120                           | 125                    |
| 245/70R17.5*<br><b>R184 Only</b>                      | DUAL   | kg.  |      |      | 1750                          | 1840 | 1940 | 2030                          | 2130                          | 2220 | 2320                          | 2420 | 2510                          | 2575(J) <sup>141</sup> |
|   |        | lb.  |      |      | 3855                          | 4060 | 4275 | 4485                          | 4700                          | 4905 | 5113                          | 5330 | 5535                          | 5675(J) <sup>141</sup> |
|   | SINGLE | kg.  |      |      | 1860                          | 1960 | 2060 | 2150                          | 2260                          | 2360 | 2470                          | 2570 | 2660                          | 2725(J) <sup>143</sup> |
|   |        | lb.  |      |      | 4110                          | 4330 | 4545 | 4750                          | 4975                          | 5210 | 5445                          | 5660 | 5865                          | 6005(J) <sup>143</sup> |
| 215/75R17.5<br><b>M729 Only</b>                       | DUAL   | kg.  |      | 1250 | 1325                          | 1400 | 1470 | 1550                          | <b>1600(F)</b> <sup>124</sup> |      |                               |      |                               |                        |
|   |        | lb.  |      | 2760 | 2920                          | 3080 | 3245 | 3420                          | <b>3525(F)</b> <sup>124</sup> |      |                               |      |                               |                        |
|   | SINGLE | kg.  |      | 1290 | 1370                          | 1450 | 1520 | 1600                          | <b>1700(F)</b> <sup>126</sup> |      |                               |      |                               |                        |
|   |        | lb.  |      | 2850 | 3015                          | 3200 | 3350 | 3530                          | <b>3750(F)</b> <sup>126</sup> |      |                               |      |                               |                        |
| 215/75R17.5<br><b>R250F</b><br>Load Range<br>"G" Only | DUAL   | kg.  |      | 1270 | 1340                          | 1405 | 1470 | 1535                          | <b>1600(G)</b> <sup>124</sup> |      |                               |      |                               |                        |
|   |        | lb.  |      | 2800 | 2950                          | 3095 | 3240 | 3385                          | <b>3525(G)</b> <sup>124</sup> |      |                               |      |                               |                        |
|   | SINGLE | kg.  |      | 1350 | 1420                          | 1495 | 1565 | 1635                          | <b>1700(G)</b> <sup>126</sup> |      |                               |      |                               |                        |
|   |        | lb.  |      | 2980 | 3135                          | 3295 | 3445 | 3600                          | <b>3750(G)</b> <sup>126</sup> |      |                               |      |                               |                        |
| 215/75R17.5*<br><b>R184 Only</b>                      | DUAL   | kg.  |      |      | 1450                          | 1520 | 1590 | 1650                          | 1720                          | 1790 | 1860                          | 1910 | 1990                          | 2060(H) <sup>133</sup> |
|   |        | lb.  |      |      | 3195                          | 3350 | 3500 | 3645                          | 3795                          | 3945 | 4095                          | 4220 | 4390                          | 4540(H) <sup>133</sup> |
|   | SINGLE | kg.  |      |      | 1530                          | 1610 | 1680 | 1750                          | 1820                          | 1900 | 1960                          | 2040 | 2110                          | 2180(H) <sup>135</sup> |
|   |        | lb.  |      |      | 3375                          | 3540 | 3695 | 3860                          | 4010                          | 4180 | 4330                          | 4495 | 4650                          | 4805(H) <sup>135</sup> |
| 225/70R19.5   | DUAL   | kg.  | 1230 | 1300 | <b>1360(E)</b> <sup>119</sup> | 1410 | 1470 | <b>1550(F)</b> <sup>123</sup> | 1580                          | 1640 | <b>1700(G)</b> <sup>126</sup> |      |                               |                        |
|   |        | lb.  | 2720 | 2860 | <b>3000(E)</b> <sup>119</sup> | 3115 | 3245 | <b>3415(F)</b> <sup>123</sup> | 3490                          | 3615 | <b>3750(G)</b> <sup>126</sup> |      |                               |                        |
|   | SINGLE | kg.  |      |      | <b>1450(E)</b> <sup>121</sup> | 1500 | 1570 | <b>1650(F)</b> <sup>125</sup> | 1690                          | 1740 | <b>1800(G)</b> <sup>128</sup> |      |                               |                        |
|   |        | lb.  |      |      | <b>3195(E)</b> <sup>121</sup> | 3315 | 3450 | <b>3640(F)</b> <sup>125</sup> | 3715                          | 3845 | <b>3970(G)</b> <sup>128</sup> |      |                               |                        |
| 245/70R19.5   | DUAL   | kg.  |      |      | 1550                          | 1590 | 1660 | <b>1750(F)</b> <sup>127</sup> | 1790                          | 1850 | <b>1950(G)</b> <sup>131</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3415                          | 3515 | 3655 | <b>3860(F)</b> <sup>127</sup> | 3940                          | 4075 | <b>4300(G)</b> <sup>131</sup> |      |                               |                        |
|   | SINGLE | kg.  |      |      | 1650                          | 1700 | 1770 | <b>1850(F)</b> <sup>129</sup> | 1900                          | 1970 | <b>2060(G)</b> <sup>133</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3640                          | 3740 | 3890 | <b>4080(F)</b> <sup>129</sup> | 4190                          | 4335 | <b>4540(G)</b> <sup>133</sup> |      |                               |                        |
| 245/70R19.5<br><b>R250F M729F</b>                     | DUAL   | kg.  |      |      | 1550                          | 1650 | 1700 | <b>1800(F)</b> <sup>128</sup> | 1850                          | 1900 | <b>2000(G)</b> <sup>134</sup> | 2060 | 2120(H) <sup>141</sup>        |                        |
|   |        | lb.  |      |      | 3415                          | 3640 | 3750 | <b>3970(F)</b> <sup>128</sup> | 4080                          | 4190 | <b>4410(G)</b> <sup>134</sup> | 4540 | <b>4675(H)</b> <sup>141</sup> |                        |
|   | SINGLE | kg.  |      |      | 1600                          | 1700 | 1750 | <b>1850(F)</b> <sup>129</sup> | 1950                          | 2000 | <b>2060(G)</b> <sup>135</sup> | 2180 | <b>2240(H)</b> <sup>144</sup> |                        |
|   |        | lb.  |      |      | 3525                          | 3750 | 3860 | <b>4080(F)</b> <sup>129</sup> | 4300                          | 4410 | <b>4540(G)</b> <sup>135</sup> | 4805 | <b>4940(H)</b> <sup>144</sup> |                        |
| 245/70R19.5<br><b>M724F Only</b>                      | DUAL   | kg.  |      |      | 1550                          | 1650 | 1660 | <b>1750(F)</b> <sup>127</sup> | 1870                          | 1990 | <b>2120(G)</b> <sup>134</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3415                          | 3650 | 3655 | <b>3860(F)</b> <sup>127</sup> | 4125                          | 4390 | <b>4675(G)</b> <sup>134</sup> |      |                               |                        |
|   | SINGLE | kg.  |      |      | 1650                          | 1700 | 1770 | <b>1850(F)</b> <sup>129</sup> | 1980                          | 2110 | <b>2240(G)</b> <sup>136</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3640                          | 3740 | 3890 | <b>4080(F)</b> <sup>129</sup> | 4370                          | 4655 | <b>4940(G)</b> <sup>136</sup> |      |                               |                        |
| 265/70R19.5<br><b>R250F Only</b>                      | DUAL   | kg.  |      |      | 1700                          | 1780 | 1860 | 1950                          | 2000                          | 2000 | <b>2180(G)</b> <sup>135</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3750                          | 3930 | 4095 | 4300                          | 4405                          | 4415 | <b>4805(G)</b> <sup>135</sup> |      |                               |                        |
|   | SINGLE | kg.  |      |      | 1800                          | 1900 | 1970 | 2060                          | 2130                          | 2200 | <b>2360(G)</b> <sup>138</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3970                          | 4180 | 4355 | 4540                          | 4685                          | 4850 | <b>5205(G)</b> <sup>138</sup> |      |                               |                        |
| 265/70R19.5<br><b>M729 Only</b>                       | DUAL   | kg.  |      |      | 1700                          | 1780 | 1860 | 1950                          | 2000                          | 2170 | <b>2360(G)</b> <sup>138</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3745                          | 3925 | 4100 | 4300                          | 4410                          | 4785 | <b>5205(G)</b> <sup>138</sup> |      |                               |                        |
|   | SINGLE | kg.  |      |      | 1800                          | 1900 | 1970 | 2060                          | 2200                          | 2340 | <b>2500(G)</b> <sup>140</sup> |      |                               |                        |
|   |        | lb.  |      |      | 3970                          | 4190 | 4345 | 4540                          | 4850                          | 5205 | <b>5510(G)</b> <sup>140</sup> |      |                               |                        |
| 285/70R19.5   | DUAL   | kg.  |      |      |                               | 1980 | 2000 | 2120                          | 2150                          | 2220 | <b>2300(G)</b> <sup>137</sup> | 2380 | 2570                          | 2725(H) <sup>143</sup> |
|   |        | lb.  |      |      |                               | 4365 | 4400 | 4675                          | 4735                          | 4900 | <b>5070(G)</b> <sup>137</sup> | 5255 | 5675                          | 6005(H) <sup>143</sup> |
|   | SINGLE | kg.  |      |      |                               | 2110 | 2190 | 2300                          | 2360                          | 2440 | <b>2500(G)</b> <sup>140</sup> | 2600 | 2800                          | 2900(H) <sup>145</sup> |
|   |        | lb.  |      |      |                               | 4645 | 4835 | 5070                          | 5205                          | 5385 | <b>5510(G)</b> <sup>140</sup> | 5740 | 6175                          | 6395(H) <sup>145</sup> |
| 305/70R19.5<br><b>R227F Only</b>                      | DUAL   | kg.  |      |      | 2060                          | 2120 | 2200 | 2300                          | 2370                          | 2450 | <b>2575(H)</b> <sup>141</sup> | 2620 | 2725                          | 2900(J) <sup>145</sup> |
|   |        | lb.  |      |      | 4540                          | 4670 | 4860 | 5070                          | 5230                          | 5410 | <b>5675(H)</b> <sup>141</sup> | 5770 | 6005                          | 6395(J) <sup>145</sup> |
|   | SINGLE | kg.  |      |      | 2240                          | 2330 | 2420 | 2500                          | 2610                          | 2700 | <b>2800(H)</b> <sup>144</sup> | 2870 | 3000                          | 3150(J) <sup>148</sup> |
|   |        | lb.  |      |      | 4940                          | 5130 | 5340 | 5510                          | 5745                          | 5945 | <b>6175(H)</b> <sup>144</sup> | 6340 | 6610                          | 6945(J) <sup>148</sup> |

\*R184 for use in free-rolling trailer service only.

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Medium Commercial Truck Radials

METRIC WIDE BASE Radial Tires for Trucks, Buses & Trailers Used in Normal Highway Service

| TIRES ARE USED AS SINGLES            |  |      |      |      |      |      |                               |       |       |                               |       |                               |       |                               |
|--------------------------------------|--|------|------|------|------|------|-------------------------------|-------|-------|-------------------------------|-------|-------------------------------|-------|-------------------------------|
| TIRE SIZE DESIGNATION                | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load) |      |      |      |      |      |                               |       |       |                               |       |                               |       |                               |
|                                      | kPa  | 480  | 520  | 550  | 590  | 620  | 660                           | 690   | 720   | 760                           | 790   | 830                           | 860   | 900                           |
|                                      | psi  | 70   | 75   | 80   | 85   | 90   | 95                            | 100   | 105   | 110                           | 115   | 120                           | 125   | 130                           |
| 445/65R19.5                          | kg.  | 3410 | 3610 | 3750 | 3960 | 4100 | 4250                          | 4410  | 4540  | <b>4750(J)</b> <sub>162</sub> |       |                               |       |                               |
|                                      | lb.  | 7540 | 7930 | 8270 | 8680 | 9040 | 9370                          | 9730  | 10100 | <b>10500(J)</b>               |       |                               |       |                               |
| 445/50R22.5                          | kg.  | 2980 | 3150 | 3330 | 3480 | 3640 | 3810                          | 3970  | 4120  | <b>4250(J)</b> <sub>158</sub> | 4430  | <b>4625(L)</b> <sub>161</sub> |       |                               |
|                                      | lb.  | 6570 | 6940 | 7310 | 7680 | 8030 | 8390                          | 8740  | 9090  | <b>9370(J)</b>                | 9780  | <b>10200(L)</b>               |       |                               |
| 455/55R22.5                          | kg.  | 3220 | 3400 | 3580 | 3760 | 3940 | 4110                          | 4280  | 4450  | <b>4625(J)</b> <sub>161</sub> | 4790  | <b>5000(L)</b> <sub>164</sub> |       | <b>5310(M)</b>                |
|                                      | lb.  | 7100 | 7500 | 7900 | 8290 | 8680 | 9060                          | 9440  | 9820  | <b>10200(J)</b>               | 10600 | <b>11000(L)</b>               |       | <b>11700(M)</b>               |
| 385/65R22.5<br>Except R244           | kg.  | 2880 | 3060 | 3150 | 3350 | 3470 | 3650                          | 3740  | 3850  | 4000                          | 4100  | <b>4250(J)</b> <sub>158</sub> |       |                               |
|                                      | lb.  | 6380 | 6720 | 6940 | 7350 | 7650 | 8050                          | 8230  | 8510  | 8820                          | 9050  | <b>9370(J)</b>                |       |                               |
| 385/65R22.5<br>R244 Only             | kg.  |      | 3060 | 3150 | 3350 | 3470 | 3650                          | 3740  | 3850  | 4000                          | 4100  | 4250                          | 4340  | <b>4500(L)</b> <sub>160</sub> |
|                                      | lb.  |      | 6720 | 6940 | 7350 | 7650 | 8050                          | 8230  | 8510  | 8820                          | 9050  | 9370                          | 9610  | <b>9920(L)</b>                |
| 425/65R22.5<br>Except R244           | kg.  | 3430 | 3640 | 3750 | 3980 | 4130 | 4250                          | 4440  | 4580  | <b>4750(J)</b> <sub>162</sub> | 4880  | <b>5150(L)</b> <sub>165</sub> |       |                               |
|                                      | lb.  | 7590 | 7990 | 8270 | 8740 | 9100 | 9370                          | 9790  | 10100 | <b>10500(J)</b>               | 10700 | <b>11400(L)</b>               |       |                               |
| 425/65R22.5<br>R244 Only             | kg.  |      | 3640 | 3750 | 3980 | 4130 | 4250                          | 4440  | 4580  | 4750                          | 4880  | <b>5150(L)</b> <sub>165</sub> |       |                               |
|                                      | lb.  |      | 7990 | 8270 | 8740 | 9100 | 9370                          | 9790  | 10100 | 10500                         | 10700 | <b>11400(L)</b>               |       |                               |
| 445/65R22.5<br>Except R244<br>& M854 | kg.  | 3720 | 3950 | 4125 | 4320 | 4470 | <b>4620(H)</b> <sub>161</sub> | 4820  | 4960  | 5150                          | 5290  | <b>5600(L)</b> <sub>168</sub> |       |                               |
|                                      | lb.  | 8230 | 8660 | 9090 | 9480 | 9870 | <b>10200(H)</b>               | 10600 | 11000 | 11400                         | 11700 | <b>12300(L)</b>               |       |                               |
| 445/65R22.5<br>R244 & M854           | kg.  |      |      | 4125 | 4320 | 4470 | 4625                          | 4820  | 4960  | 5150                          | 5290  | 5600                          | 5700  | <b>5800(M)</b> <sub>169</sub> |
|                                      | lb.  |      |      | 9090 | 9480 | 9870 | 10200                         | 10600 | 11000 | 11400                         | 11700 | 12300                         | 12600 | <b>12800(M)</b>               |

## Radial Ply METRIC Tires for Trucks, Buses & Trailers Used in Normal Highway Service

| TIRES MOUNTED ON 15° DROP CENTER RIMS             |        |   |     |      |      |      |      |      |      |                               |      |                               |                               |                               |
|---|--------|---|-----|------|------|------|------|------|------|-------------------------------|------|-------------------------------|-------------------------------|-------------------------------|
| TIRE SIZE DESIGNATION                             | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures. Pressure Listed is the Minimum for the Load |     |      |      |      |      |      |      |                               |      |                               |                               |                               |
|   |        | kPa   | 520 | 550  | 590  | 620  | 660  | 690  | 720  | 760                           | 790  | 830                           | 860                           | 900                           |
|   |        | psi   | 75  | 80   | 85   | 90   | 95   | 100  | 105  | 110                           | 115  | 120                           | 125                           | 130                           |
| 255/70R22.5                                       | DUAL   | kg.   |     | 1800 | 1860 | 1940 | 2000 | 2020 | 2090 | <b>2120(G)</b> <sub>134</sub> | 2230 | <b>2300(H)</b> <sub>137</sub> |                               |                               |
|   |        | lb.   |     | 3970 | 4110 | 4275 | 4410 | 4455 | 4610 | 4675                          | 4915 | <b>5070(H)</b> <sub>137</sub> |                               |                               |
|   | SINGLE | kg.   |     | 1900 | 1980 | 2060 | 2120 | 2220 | 2300 | <b>2360(G)</b> <sub>138</sub> | 2450 | <b>2500(H)</b> <sub>140</sub> |                               |                               |
|   |        | lb.   |     | 4190 | 4370 | 4550 | 4675 | 4895 | 5065 | 5205                          | 5400 | <b>5510(H)</b> <sub>140</sub> |                               |                               |
| 275/70R22.5<br>R192<br>Load Range<br>"J" Only     | DUAL   | kg.   |     |      | 2170 | 2260 | 2340 | 2430 | 2510 | 2650                          | 2680 | 2760                          | <b>2900(J)</b> <sub>145</sub> |                               |
|   |        | lb.   |     |      | 4785 | 4980 | 5160 | 5355 | 5535 | 5840                          | 5910 | 6085                          | <b>6395(J)</b> <sub>145</sub> |                               |
|   | SINGLE | kg.   |     |      | 2380 | 2480 | 2570 | 2670 | 2760 | 2900                          | 2940 | 3030                          | <b>3150(J)</b> <sub>148</sub> |                               |
|   |        | lb.   |     |      | 5245 | 5465 | 5665 | 5885 | 6085 | 6395                          | 6480 | 6680                          | <b>6940(J)</b> <sub>148</sub> |                               |
| 275/70R22.5<br>R250F/ED<br>Load Range<br>"J" Only | DUAL   | kg.   |     |      | 2180 | 2300 | 2430 | 2500 | 2575 | 2725                          | 2800 | <b>2900(J)</b> <sub>145</sub> |                               |                               |
|   |        | lb.   |     |      | 4805 | 5070 | 5355 | 5510 | 5675 | 6005                          | 6175 | <b>6395(J)</b> <sub>145</sub> |                               |                               |
|   | SINGLE | kg.   |     |      | 2430 | 2500 | 2650 | 2725 | 2900 | 3000                          | 3075 | <b>3175(J)</b> <sub>148</sub> |                               |                               |
|   |        | lb.   |     |      | 5355 | 5510 | 5840 | 6005 | 6395 | 6610                          | 6940 | <b>7000(J)</b> <sub>148</sub> |                               |                               |
| 275/70R22.5<br>M840<br>Load Range<br>"J" Only     | DUAL   | kg.   |     |      | 2180 | 2300 | 2430 | 2500 | 2575 | 2725                          | 2800 | <b>2900(J)</b> <sub>145</sub> |                               |                               |
|   |        | lb.   |     |      | 4805 | 5070 | 5355 | 5510 | 5675 | 6005                          | 6175 | <b>6395(J)</b> <sub>145</sub> |                               |                               |
|   | SINGLE | kg.   |     |      | 2360 | 2500 | 2650 | 2725 | 2800 | 2900                          | 3075 | <b>3150(J)</b> <sub>148</sub> |                               |                               |
|   |        | lb.   |     |      | 5205 | 5510 | 5840 | 6005 | 6175 | 6395                          | 6780 | <b>6940(J)</b> <sub>148</sub> |                               |                               |
| 305/70R22.5<br>R192<br>Load Range<br>"L" Only     | DUAL   | kg.   |     | 2180 | 2300 | 2430 | 2500 | 2650 | 2725 | 2800                          | 2900 | 3075                          | 3150                          | <b>3150(L)</b> <sub>148</sub> |
|   |        | lb.   |     | 4805 | 5070 | 5355 | 5510 | 5840 | 6005 | 6395                          | 6610 | 6780                          | 6940                          | <b>6940(L)</b>                |
|   | SINGLE | kg.   |     | 2500 | 2575 | 2725 | 2900 | 3000 | 3075 | 3250                          | 3350 | 3450                          | 3550                          | <b>3550(L)</b> <sub>152</sub> |
|   |        | lb.   |     | 5510 | 5675 | 6005 | 6395 | 6610 | 6780 | 7160                          | 7390 | 7610                          | 7830                          | <b>7830(L)</b>                |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Medium Commercial Truck Radials

Radial Ply METRIC Tires for Trucks, Buses & Trailers Used in Normal Highway Service

| TIRES MOUNTED ON 15° DROP CENTER RIMS                  |        |  |      |      |      |      |      |      |      |      |                        |      |                        |     |
|--|--------|--|------|------|------|------|------|------|------|------|------------------------|------|------------------------|-----|
| TIRE SIZE DESIGNATION                                  | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load) |      |      |      |      |      |      |      |      |                        |      |                        |     |
|  |        | kPa  | 480  | 520  | 550  | 590  | 620  | 660  | 690  | 720  | 760                    | 790  | 830                    | 860 |
|  |        | psi  | 70   | 75   | 80   | 85   | 90   | 95   | 100  | 105  | 110                    | 115  | 120                    | 125 |
| 245/75R22.5  | DUAL   | kg.  | 1430 | 1500 | 1600 | 1640 | 1710 | 1800 | 1840 | 1900 | 1950(G) <sup>131</sup> |      |                        |     |
|  |        | lb.  | 3160 | 3315 | 3525 | 3615 | 3765 | 3970 | 4055 | 4195 | 4300(G) <sup>131</sup> |      |                        |     |
|  | SINGLE | kg.  | 1570 | 1650 | 1750 | 1800 | 1880 | 1950 | 2020 | 2090 | 2120(G) <sup>134</sup> |      |                        |     |
|  |        | lb.  | 3470 | 3645 | 3860 | 3975 | 4140 | 4300 | 4455 | 4610 | 4675(G) <sup>134</sup> |      |                        |     |
| 265/75R22.5  | DUAL   | kg.  | 1600 | 1680 | 1750 | 1830 | 1910 | 2000 | 2050 | 2130 | 2180(G) <sup>131</sup> |      |                        |     |
|  |        | lb.  | 3525 | 3705 | 3860 | 4040 | 4205 | 4410 | 4525 | 4685 | 4805(G) <sup>131</sup> |      |                        |     |
|  | SINGLE | kg.  | 1760 | 1850 | 1950 | 2010 | 2100 | 2180 | 2260 | 2340 | 2360(G) <sup>138</sup> |      |                        |     |
|  |        | lb.  | 3875 | 4070 | 4300 | 4440 | 4620 | 4805 | 4975 | 5150 | 5205(G) <sup>138</sup> |      |                        |     |
| 295/75R22.5<br><b>R283<br/>Load Range<br/>"H" Only</b> | DUAL   | kg.  | 2030 | 2130 | 2240 | 2320 | 2420 | 2500 | 2600 | 2690 | 2800                   | 2870 | 3000(H) <sup>143</sup> |     |
|  |        | lb.  | 4470 | 4690 | 4940 | 5120 | 5330 | 5510 | 5740 | 5940 | 6175                   | 6330 | 6610(H) <sup>143</sup> |     |
|  | SINGLE | kg.  | 2230 | 2340 | 2430 | 2550 | 2660 | 2725 | 2860 | 2960 | 3075                   | 3150 | 3250(H) <sup>148</sup> |     |
|  |        | lb.  | 4915 | 5155 | 5355 | 5630 | 5860 | 6005 | 6305 | 6525 | 6780                   | 6950 | 7160(H) <sup>148</sup> |     |
| 295/75R22.5  | DUAL   | kg.  | 1860 | 1950 | 2060 | 2130 | 2220 | 2300 | 2390 | 2470 | 2575(G) <sup>141</sup> | 2630 | 2725(H) <sup>143</sup> |     |
|  |        | lb.  | 4095 | 4300 | 4540 | 4690 | 4885 | 5070 | 5260 | 5440 | 5675(G) <sup>141</sup> | 5795 | 6005(H) <sup>143</sup> |     |
|  | SINGLE | kg.  | 2040 | 2140 | 2240 | 2340 | 2440 | 2500 | 2620 | 2710 | 2800(G) <sup>144</sup> | 2890 | 3000(H) <sup>146</sup> |     |
|  |        | lb.  | 4500 | 4725 | 4940 | 5155 | 5370 | 5510 | 5780 | 5980 | 6175(G) <sup>144</sup> | 6370 | 6610(H) <sup>146</sup> |     |

|                                  |        | kPa | 520 | 550  | 590  | 620  | 660  | 690  | 720  | 760  | 790  | 830                    | 860                    | 900                    |
|----------------------------------|--------|-----|-----|------|------|------|------|------|------|------|------|------------------------|------------------------|------------------------|
|                                  |        | psi | 75  | 80   | 85   | 90   | 95   | 100  | 105  | 110  | 115  | 120                    | 125                    | 130                    |
|                                  |        |     |     |      |      |      |      |      |      |      |      |                        |                        |                        |
| 295/60R22.5                      | DUAL   | kg. |     |      | 2190 | 2290 | 2395 | 2495 | 2595 | 2690 | 2790 | 2885                   | 2980                   | 3075(J) <sup>147</sup> |
|                                  |        | lb. |     |      | 4825 | 5050 | 5275 | 5495 | 5715 | 5930 | 6145 | 6360                   | 6570                   | 6780(J) <sup>147</sup> |
|                                  | SINGLE | kg. |     |      | 2385 | 2495 | 2610 | 2715 | 2825 | 2930 | 3040 | 3145                   | 3230                   | 3350(J) <sup>150</sup> |
|                                  |        | lb. |     |      | 5260 | 5505 | 5750 | 5990 | 6230 | 6465 | 6700 | 6930                   | 7160                   | 7390(J) <sup>150</sup> |
| 295/80R22.5<br><b>R250F Only</b> | DUAL   | kg. |     | 2180 | 2300 | 2420 | 2540 | 2660 | 2780 | 2900 | 3075 | 3115                   | 3150(H) <sup>148</sup> |                        |
|                                  |        | lb. |     | 4810 | 5080 | 5340 | 600  | 5860 | 6130 | 6390 | 6780 | 6860                   | 6940(H) <sup>148</sup> |                        |
|                                  | SINGLE | kg. |     | 2430 | 2560 | 2690 | 2820 | 2950 | 3090 | 3220 | 3350 | 3455                   | 3550(H) <sup>152</sup> |                        |
|                                  |        | lb. |     | 5350 | 5640 | 5930 | 6220 | 6510 | 6810 | 7100 | 7390 | 7610                   | 7830(H) <sup>152</sup> |                        |
| 315/80R22.5                      | DUAL   | kg. |     | 2575 | 2650 | 2750 | 2900 | 2970 | 3070 | 3150 | 3270 | 3450(J) <sup>151</sup> | 3590                   | 3750(L) <sup>154</sup> |
|                                  |        | lb. |     | 5675 | 5840 | 6070 | 6395 | 6545 | 6770 | 6940 | 7210 | 7610(J) <sup>151</sup> | 7910                   | 8270(L) <sup>154</sup> |
|                                  | SINGLE | kg. |     | 2800 | 2910 | 3030 | 3150 | 3260 | 3370 | 3450 | 3590 | 3750(J) <sup>154</sup> | 3940                   | 4125(L) <sup>157</sup> |
|                                  |        | lb. |     | 6175 | 6415 | 6670 | 6940 | 7190 | 7440 | 7610 | 7920 | 8270(J) <sup>154</sup> | 8690                   | 9090(L) <sup>157</sup> |
| 315/80R22.5<br><b>M860A Only</b> | DUAL   | kg. |     | 2575 | 2650 | 2750 | 2900 | 2970 | 3070 | 3150 | 3270 | 3450(J) <sup>151</sup> | 3795                   | 4125(L) <sup>157</sup> |
|                                  |        | lb. |     | 5675 | 5840 | 6070 | 6395 | 6545 | 6770 | 6940 | 7210 | 7610(J) <sup>151</sup> | 8350                   | 9090(L) <sup>157</sup> |
|                                  | SINGLE | kg. |     | 2800 | 2910 | 3030 | 3150 | 3260 | 3370 | 3450 | 3590 | 3750(J) <sup>154</sup> | 4150                   | 4355(L)                |
|                                  |        | lb. |     | 6175 | 6415 | 6670 | 6940 | 7190 | 7440 | 7610 | 7920 | 8270(J) <sup>154</sup> | 9135                   | 10000(L)               |
| 315/80R22.5<br><b>R249 Only</b>  | Dual   | kg. |     | 2575 | 2650 | 2750 | 2900 | 2970 | 3070 | 3150 | 3270 | 3450(J) <sup>151</sup> | 3725                   | 4000(L) <sup>156</sup> |
|                                  |        | lb. |     | 5675 | 5840 | 6070 | 6395 | 6545 | 6770 | 6940 | 7210 | 7610(J) <sup>151</sup> | 8215                   | 8820(L)                |
|                                  | Single | kg. |     | 2800 | 2910 | 3030 | 3150 | 3260 | 3370 | 3450 | 3590 | 3750(J) <sup>154</sup> | 4000                   | 4250(L) <sup>158</sup> |
|                                  |        | lb. |     | 6175 | 6415 | 6670 | 6940 | 7190 | 7440 | 7610 | 7920 | 8270(J) <sup>154</sup> | 8820                   | 9370(L)                |

|                                 |        | kPa | 480  | 520  | 550  | 590  | 620  | 660                    | 690  | 720  | 760                    | 790  | 830                    | 860                    |
|---------------------------------|--------|-----|------|------|------|------|------|------------------------|------|------|------------------------|------|------------------------|------------------------|
|                                 |        | psi | 70   | 75   | 80   | 85   | 90   | 95                     | 100  | 105  | 110                    | 115  | 120                    | 125                    |
|                                 |        |     |      |      |      |      |      |                        |      |      |                        |      |                        |                        |
| 285/75R24.5                     | DUAL   | kg. | 1870 | 1970 | 2060 | 2150 | 2240 | 2360(F) <sup>138</sup> | 2410 | 2490 | 2575(G) <sup>141</sup> | 2660 | 2800(H) <sup>144</sup> |                        |
|                                 |        | lb. | 1435 | 4340 | 4540 | 4740 | 4930 | 5310                   | 5310 | 5495 | 5675(G) <sup>141</sup> | 5860 | 6175(H) <sup>144</sup> |                        |
|                                 | SINGLE | kg. | 2060 | 2160 | 2240 | 2360 | 2460 | 2575(F) <sup>141</sup> | 2650 | 2740 | 2800(G) <sup>144</sup> | 2920 | 3075(H) <sup>147</sup> |                        |
|                                 |        | lb. | 4545 | 4770 | 4940 | 5210 | 5420 | 5675(F) <sup>141</sup> | 5835 | 6040 | 6175(G) <sup>144</sup> | 6440 | 6780(H) <sup>147</sup> |                        |
| 305/75R24.5<br><b>R294 Only</b> | DUAL   | kg. |      |      | 2170 | 2290 | 2400 | 2520                   | 2660 | 2640 | 2760                   | 2880 | 3010                   | 3250(J) <sup>148</sup> |
|                                 |        | lb. |      |      | 4780 | 5040 | 5300 | 5560                   | 5860 | 5820 | 6090                   | 6340 | 6640                   | 6945(J) <sup>148</sup> |
|                                 | SINGLE | kg. |      |      | 2380 | 2510 | 2640 | 2770                   | 2900 | 3030 | 3160                   | 3290 | 3420                   | 3550(J) <sup>152</sup> |
|                                 |        | lb. |      |      | 5251 | 5540 | 5820 | 6110                   | 6400 | 6680 | 6970                   | 7260 | 7540                   | 7830(J) <sup>152</sup> |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum. International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Medium Commercial Truck Radials

Radial Ply Tires for Trucks, Buses & Trailers Used in Normal Highway Service

## TIRES MOUNTED ON 15° DROP CENTER RIMS

| TIRE SIZE DESIGNATION         | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load) |                               |      |      |                               |                               |                               |      |                               |      |      |                               |
|-------------------------------|--------|--|-------------------------------|------|------|-------------------------------|-------------------------------|-------------------------------|------|-------------------------------|------|------|-------------------------------|
|                               |        | kPa  | 590                           | 620  | 660  | 690                           | 720                           | 760                           | 790  | 830                           | 860  | 900  | 930                           |
|                               |        | psi  | 85                            | 90   | 95   | 100                           | 105                           | 110                           | 115  | 120                           | 125  | 130  | 135                           |
| 9R17.5HC                      | DUAL   | kg.  | 1380                          | 1430 | 1480 | 1520                          | <b>1600(F)</b> <sub>124</sub> | 1650                          | 1700 | <b>1750(G)</b> <sub>127</sub> | 1800 | 1850 | <b>1900(H)</b> <sub>130</sub> |
|                               |        | lb.  | 3040                          | 3150 | 3260 | 3360                          | <b>3525(F)</b>                | 3635                          | 3745 | <b>3860(G)</b>                | 3970 | 4080 | <b>4190(H)</b>                |
|                               | SINGLE | kg.  | 1450                          | 1520 | 1570 | 1630                          | <b>1700(F)</b> <sub>126</sub> | 1750                          | 1800 | <b>1850(G)</b> <sub>129</sub> | 1900 | 1950 | <b>2000(H)</b> <sub>132</sub> |
|                               |        | lb.  | 3200                          | 3340 | 3470 | 3590                          | <b>3750(F)</b>                | 3860                          | 3970 | <b>4080(G)</b>                | 4190 | 4300 | <b>4410(H)</b>                |
| 10R17.5HC<br><b>R180 Only</b> | DUAL   | kg.  | <b>1650(E)</b> <sub>125</sub> | 1720 | 1790 | <b>1850(F)</b> <sub>126</sub> | 1920                          | <b>2000(H)</b> <sub>132</sub> |      |                               |      |      |                               |
|                               |        | lb.  | <b>3640(E)</b>                | 3785 | 3930 | <b>4080(F)</b>                | 4235                          | <b>4410(H)</b>                |      |                               |      |      |                               |
|                               | SINGLE | kg.  | <b>1750(E)</b> <sub>127</sub> | 1820 | 1890 | <b>1950(F)</b> <sub>131</sub> | 2030                          | <b>2120(H)</b> <sub>134</sub> |      |                               |      |      |                               |
|                               |        | lb.  | <b>3860(E)</b>                | 4005 | 4150 | <b>4300(F)</b>                | 4470                          | <b>4675(H)</b>                |      |                               |      |      |                               |

| TIRE SIZE DESIGNATION | USAGE  | kPa | 480  | 520  | 550                           | 590                           | 620                           | 660                           | 690                           | 720                           | 760                           | 790                           | 830                           |
|-----------------------|--------|-----|------|------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
|                       |        | psi | 70   | 75   | 80                            | 85                            | 90                            | 95                            | 100                           | 105                           | 110                           | 115                           | 120                           |
|                       |        |     |      |      |                               |                               |                               |                               |                               |                               |                               |                               |                               |
| 8R19.5                | DUAL   | kg. | 1120 | 1170 | <b>1215(D)</b> <sub>115</sub> | 1285                          | 1310                          | <b>1360(E)</b> <sub>119</sub> | 1410                          | 1460                          | <b>1500(F)</b> <sub>122</sub> |                               |                               |
|                       |        | lb. | 2460 | 2570 | <b>2680(D)</b>                | 2785                          | 2890                          | <b>3000(E)</b>                | 3100                          | 3200                          | <b>3305(F)</b>                |                               |                               |
|                       | SINGLE | kg. | 1150 | 1220 | <b>1285(D)</b> <sub>117</sub> | 1340                          | 1400                          | <b>1450(E)</b> <sub>121</sub> | 1500                          | 1550                          | <b>1600(F)</b> <sub>124</sub> |                               |                               |
|                       |        | lb. | 2540 | 2680 | <b>2835(D)</b>                | 2955                          | 3075                          | <b>3195(E)</b>                | 3305                          | 3415                          | <b>3525(F)</b>                |                               |                               |
| 9R22.5                | DUAL   | kg. | 1480 | 1550 | 1610                          | 1670                          | <b>1750(E)</b> <sub>127</sub> | 1820                          | 1890                          | <b>1950(F)</b> <sub>131</sub> | 2010                          | 2070                          | <b>2210(G)</b> <sub>134</sub> |
|                       |        | lb. | 3270 | 3410 | 3550                          | 3690                          | <b>3860(E)</b>                | 4005                          | 4150                          | <b>4300(F)</b>                | 4425                          | 4550                          | <b>4675(G)</b>                |
|                       | SINGLE | kg. | 1530 | 1610 | 1690                          | 1760                          | <b>1850(F)</b> <sub>129</sub> | 1920                          | 1990                          | <b>2060(F)</b> <sub>133</sub> | 2120                          | 2180                          | <b>2240(G)</b> <sub>136</sub> |
|                       |        | lb. | 3370 | 3560 | 3730                          | 3890                          | <b>4080(E)</b>                | 4235                          | 4390                          | <b>4540(F)</b>                | 4675                          | 4810                          | <b>4940(G)</b>                |
| 10R22.5               | DUAL   | kg. | 1750 | 1830 | 1910                          | <b>2000(E)</b> <sub>132</sub> | 2080                          | 2160                          | <b>2240(F)</b> <sub>136</sub> | 2300                          | 2360                          | <b>2430(G)</b> <sub>139</sub> |                               |
|                       |        | lb. | 3860 | 4045 | 4230                          | <b>4410(E)</b>                | 4585                          | 4760                          | <b>4940(F)</b>                | 5075                          | 5210                          | <b>5355(G)</b>                |                               |
|                       | SINGLE | kg. | 1850 | 1940 | 2030                          | <b>2120(E)</b> <sub>134</sub> | 2200                          | 2280                          | <b>2360(F)</b> <sub>138</sub> | 2430                          | 2500                          | <b>2575(G)</b> <sub>141</sub> |                               |
|                       |        | lb. | 4080 | 4280 | 4480                          | <b>4675(E)</b>                | 4850                          | 5025                          | <b>5205(F)</b>                | 5360                          | 5515                          | <b>5675(G)</b>                |                               |
| 11R22.5               | DUAL   | kg. | 1990 | 2080 | 2160                          | 2250                          | <b>2360(F)</b> <sub>138</sub> | 2460                          | 2560                          | <b>2650(G)</b> <sub>142</sub> | 2680                          | 2710                          | <b>2725(H)</b> <sub>143</sub> |
|                       |        | lb. | 4380 | 4580 | 4760                          | 4950                          | <b>5205(F)</b>                | 5415                          | 5625                          | <b>5840(G)</b>                | 5895                          | 5950                          | <b>6005(H)</b>                |
|                       | SINGLE | kg. | 2050 | 2160 | 2260                          | 2370                          | <b>2500(F)</b> <sub>140</sub> | 2600                          | 2700                          | <b>2800(G)</b> <sub>144</sub> | 2870                          | 2940                          | <b>3000(H)</b> <sub>146</sub> |
|                       |        | lb. | 4560 | 4770 | 4990                          | 5220                          | <b>5510(F)</b>                | 5730                          | 5950                          | <b>6175(G)</b>                | 6320                          | 6465                          | <b>6610(H)</b>                |
| 11R24.5               | DUAL   | kg. | 2110 | 2210 | 2300                          | 2390                          | <b>2500(F)</b> <sub>140</sub> | 2580                          | 2660                          | <b>2725(G)</b> <sub>143</sub> | 2820                          | 2910                          | <b>3000(H)</b> <sub>146</sub> |
|                       |        | lb. | 4660 | 4870 | 5070                          | 5260                          | <b>5510(F)</b>                | 5675                          | 5840                          | <b>6005(G)</b>                | 6205                          | 6405                          | <b>6610(H)</b>                |
|                       | SINGLE | kg. | 2190 | 2300 | 2410                          | 2520                          | <b>2650(F)</b> <sub>142</sub> | 2770                          | 2890                          | <b>3000(G)</b> <sub>146</sub> | 3080                          | 3160                          | <b>3250(H)</b> <sub>149</sub> |
|                       |        | lb. | 4820 | 5070 | 5310                          | 5550                          | <b>5840(F)</b>                | 6095                          | 6350                          | <b>6610(G)</b>                | 6790                          | 6970                          | <b>7160(H)</b>                |
| 12R22.5               | DUAL   | kg. | 2170 | 2260 | 2350                          | 2440                          | <b>2575(F)</b> <sub>141</sub> | 2630                          | 2680                          | <b>2725(G)</b> <sub>143</sub> | 2840                          | 2960                          | <b>3075(H)</b> <sub>147</sub> |
|                       |        | lb. | 4780 | 4990 | 5190                          | 5390                          | <b>5675(F)</b>                | 5785                          | 5895                          | <b>6005(G)</b>                | 6265                          | 6525                          | <b>6780(H)</b>                |
|                       | SINGLE | kg. | 2240 | 2360 | 2470                          | 2580                          | <b>2725(F)</b> <sub>141</sub> | 2820                          | 2910                          | <b>3000(G)</b> <sub>146</sub> | 3120                          | 3240                          | <b>3350(H)</b> <sub>150</sub> |
|                       |        | lb. | 4940 | 5200 | 5450                          | 5690                          | <b>6005(F)</b>                | 6205                          | 6405                          | <b>6610(G)</b>                | 6870                          | 7130                          | <b>7390(H)</b>                |
| 12R24.5               | DUAL   | kg. | 2300 | 2400 | 2500                          | 2600                          | <b>2650(F)</b> <sub>142</sub> | 2770                          | 2890                          | <b>3000(G)</b> <sub>146</sub> | 3080                          | 3160                          | <b>3250(H)</b> <sub>149</sub> |
|                       |        | lb. | 5080 | 5300 | 5520                          | 5730                          | <b>5840(F)</b>                | 6095                          | 6350                          | <b>6610(G)</b>                | 6790                          | 6970                          | <b>7160(H)</b>                |
|                       | SINGLE | kg. | 2380 | 2500 | 2630                          | 2740                          | <b>2900(F)</b> <sub>145</sub> | 3020                          | 3140                          | <b>3250(G)</b> <sub>152</sub> | 3350                          | 3450                          | <b>3550(H)</b> <sub>152</sub> |
|                       |        | lb. | 5240 | 5520 | 5790                          | 6040                          | <b>6395(F)</b>                | 6650                          | 6910                          | <b>7160(G)</b>                | 7380                          | 7600                          | <b>7830(H)</b>                |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Medium Commercial Truck Radials

Radial Ply Tires for Trucks, Buses & Trailers Used in Normal Highway Service

## TIRES MOUNTED ON FLAT BASE RIMS

| TIRE SIZE DESIGNATION | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load) |      |      |      |      |                              |                              |      |                              |                              |      |                              |
|-----------------------|--------|--|------|------|------|------|------------------------------|------------------------------|------|------------------------------|------------------------------|------|------------------------------|
|                       |        | kPa  | 480  | 520  | 550  | 590  | 620                          | 660                          | 690  | 720                          | 760                          | 790  | 830                          |
|                       |        | psi  | 70   | 75   | 80   | 85   | 90                           | 95                           | 100  | 105                          | 110                          | 115  | 120                          |
| 8.25R15TR             | DUAL   | kg.  | 1220 | 1270 | 1330 | 1380 | 1430                         | 1480                         | 1520 | <b>1600(F)<sub>124</sub></b> | 1650                         | 1700 | <b>1750(G)<sub>127</sub></b> |
|                       |        | lb.  | 2700 | 2810 | 2930 | 3040 | 3150                         | 3260                         | 3360 | <b>3525(F)</b>               | 3635                         | 3745 | <b>3860(G)</b>               |
|                       | SINGLE | kg.  | 1260 | 1330 | 1400 | 1450 | 1520                         | 1570                         | 1630 | <b>1700(F)<sub>126</sub></b> | 1750                         | 1800 | <b>1850(G)<sub>129</sub></b> |
|                       |        | lb.  | 2780 | 2930 | 3080 | 3200 | 3340                         | 3470                         | 3690 | <b>3750(F)</b>               | 3860                         | 3970 | <b>4080(G)</b>               |
| 10.00R15TR            | DUAL   | kg.  | 1660 | 1740 | 1810 | 1870 | <b>1950(F)<sub>131</sub></b> | 2030                         | 2110 | <b>2180(G)<sub>135</sub></b> | 2260                         | 2340 | <b>2430(H)<sub>139</sub></b> |
|                       |        | lb.  | 3660 | 3830 | 3980 | 4130 | <b>4300(F)<sub>131</sub></b> | 4470                         | 4640 | <b>4805(G)<sub>135</sub></b> | 4990                         | 5175 | <b>5355(H)<sub>139</sub></b> |
|                       | SINGLE | kg.  | 1710 | 1810 | 1890 | 1980 | <b>2060(F)<sub>133</sub></b> | 2140                         | 2220 | <b>2300(G)<sub>140</sub></b> | 2390                         | 2480 | <b>2575(H)<sub>141</sub></b> |
|                       |        | lb.  | 3780 | 3980 | 4170 | 4370 | <b>4540(F)<sub>133</sub></b> | 4715                         | 4890 | <b>5070(G)<sub>140</sub></b> | 5270                         | 5470 | <b>5675(H)<sub>141</sub></b> |
| 11.00R24              | DUAL   | kg.  | 2440 | 2550 | 2660 | 2760 | <b>2800(F)<sub>144</sub></b> | 2920                         | 3040 | <b>3150(G)<sub>148</sub></b> | 3250                         | 3350 | <b>3450(H)<sub>151</sub></b> |
|                       |        | lb.  | 5390 | 5630 | 5860 | 6090 | <b>6175(F)<sub>144</sub></b> | 6430                         | 6690 | <b>6940(G)</b>               | 7160                         | 7380 | <b>7610(H)</b>               |
|                       | SINGLE | kg.  | 2440 | 2550 | 2660 | 2760 | <b>3075(F)<sub>147</sub></b> | 3200                         | 3330 | <b>3450(G)<sub>151</sub></b> | 3550                         | 3650 | <b>3750(H)<sub>154</sub></b> |
|                       |        | lb.  | 5390 | 5630 | 5860 | 6090 | <b>6780(F)<sub>147</sub></b> | 7060                         | 7340 | <b>7610(G)</b>               | 7830                         | 8050 | <b>8270(H)</b>               |
| 12.00R24              | DUAL   | kg.  | 2780 | 2860 | 3020 | 3140 | 3250                         | <b>3350(G)<sub>150</sub></b> | 3450 | 3550                         | <b>3650(H)<sub>153</sub></b> | 3760 | <b>3875(J)<sub>155</sub></b> |
|                       |        | lb.  | 6120 | 6390 | 6650 | 6910 | 7160                         | <b>7390(G)<sub>150</sub></b> | 7610 | 7830                         | <b>8050(H)<sub>153</sub></b> | 8300 | <b>8540(J)</b>               |
|                       | SINGLE | kg.  | 2870 | 3020 | 3170 | 3300 | 3440                         | <b>3650(G)<sub>153</sub></b> | 3770 | 3890                         | <b>4000(H)<sub>156</sub></b> | 4130 | <b>4250(J)<sub>158</sub></b> |
|                       |        | lb.  | 6330 | 6660 | 6980 | 7280 | 7580                         | <b>8050(G)</b>               | 8310 | 8570                         | <b>8820(H)</b>               | 9100 | <b>9370(J)</b>               |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Commercial Light Truck Radials

Light Truck **METRIC** Radial Ply Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service

## TIRES MOUNTED ON 5° DROP CENTER RIMS

| TIRE SIZE DESIGNATION | USAGE  | Tire Load Limits (lb.) at various Cold Inflation Pressures |      |      |      |                              |      |      |                              |      |      |                              |
|-----------------------|--------|--|------|------|------|------------------------------|------|------|------------------------------|------|------|------------------------------|
|                       |        | kPa  | 250  | 275  | 300  | 350                          | 380  | 400  | 450                          | 480  | 500  | 550                          |
|                       |        | psi  | 35   | 40   | 45   | 50                           | 55   | 60   | 65                           | 70   | 75   | 80                           |
| LT275/65R18           | DUAL   | kg.  | 820  | 880  | 930  | <b>1060(C)<sub>110</sub></b> | 1095 | 1140 | 1250                         | 1300 | 1130 | <b>1400(E)<sub>120</sub></b> |
|                       |        | lb.  | 1765 | 1940 | 2100 | <b>2335(C)</b>               | 2420 | 2570 | 2755                         | 2865 | 3010 | <b>3085(E)</b>               |
|                       | SINGLE | kg.  | 900  | 965  | 1020 | <b>1150(C)<sub>113</sub></b> | 1205 | 1250 | 1360                         | 1425 | 1450 | <b>1550(E)<sub>123</sub></b> |
|                       |        | lb.  | 1940 | 2130 | 2310 | <b>2535(C)</b>               | 2660 | 2825 | 3000                         | 3150 | 3305 | <b>3415(E)</b>               |
| LT245/70R17           | DUAL   | kg.  | 715  | 765  | 810  | <b>900(C)<sub>104</sub></b>  | 955  | 990  | <b>1060(D)<sub>110</sub></b> | 1130 | 1160 | <b>1250(E)<sub>116</sub></b> |
|                       |        | lb.  | 1540 | 1690 | 1830 | <b>1985(C)</b>               | 2105 | 2240 | <b>2335(D)</b>               | 2495 | 2615 | <b>2755(E)</b>               |
|                       | SINGLE | kg.  | 785  | 840  | 890  | <b>1000(C)<sub>108</sub></b> | 1050 | 1090 | <b>1180(D)<sub>114</sub></b> | 1240 | 1270 | <b>1360(E)<sub>119</sub></b> |
|                       |        | lb.  | 1690 | 1855 | 2010 | <b>2205(C)</b>               | 2315 | 2460 | <b>2600(D)</b>               | 2740 | 2875 | <b>3000(E)</b>               |
| LT265/70R17           | DUAL   | kg.  | 800  | 855  | 910  | <b>1030(C)<sub>109</sub></b> | 1070 | 1110 | <b>1060(D)<sub>110</sub></b> | 1240 | 1260 | <b>1320(E)<sub>118</sub></b> |
|                       |        | lb.  | 1720 | 1890 | 2050 | <b>2270(C)</b>               | 2360 | 2510 | <b>2680(D)</b>               | 2735 | 2820 | <b>2910(E)</b>               |
|                       | SINGLE | kg.  | 880  | 920  | 1000 | <b>1120(C)<sub>112</sub></b> | 1175 | 1220 | <b>1215(D)<sub>114</sub></b> | 1360 | 1390 | <b>1450(E)<sub>119</sub></b> |
|                       |        | lb.  | 1890 | 2075 | 2255 | <b>2470(C)</b>               | 2595 | 2760 | <b>2910(D)</b>               | 3005 | 3100 | <b>3195(E)</b>               |

| TIRE SIZE DESIGNATION | USAGE | kPa         | 480  | 520  | 550                         | 590  | 620                          | 660  | 690                          |
|-----------------------|-------|-------------|------|------|-----------------------------|------|------------------------------|------|------------------------------|
|                       |       | psi         | 70   | 75   | 80                          | 85   | 90                           | 95   | 100                          |
|                       |       | LT235/75R15 | DUAL | kg.  | 645                         | 735  | <b>825(C)<sub>101</sub></b>  | 900  | <b>975(D)<sub>107</sub></b>  |
| lb.                   | 1420  |             |      | 1620 | <b>1820(C)</b>              | 1985 | <b>2150(D)</b>               | 2335 | <b>2535(E)</b>               |
| SINGLE                | kg.   |             | 710  | 810  | <b>900(C)<sub>104</sub></b> | 990  | <b>1060(D)<sub>110</sub></b> | 1160 | <b>1250(E)<sub>116</sub></b> |
|                       | lb.   |             | 1565 | 1785 | <b>1985(C)</b>              | 2180 | <b>2335(D)</b>               | 2555 | <b>2755(E)</b>               |

| TIRE SIZE DESIGNATION | USAGE  | kPa         | 250  | 280  | 310  | 350                          | 380  | 410                         | 450                          | 480  | 520                         | 550                          |
|-----------------------|--------|-------------|------|------|------|------------------------------|------|-----------------------------|------------------------------|------|-----------------------------|------------------------------|
|                       |        | psi         | 35   | 40   | 45   | 50                           | 55   | 60                          | 65                           | 70   | 75                          | 80                           |
|                       |        | LT225/75R16 | DUAL | kg.  | 635  | 675                          | 725  | <b>800(C)<sub>100</sub></b> | 945                          | 885  | <b>975(D)<sub>107</sub></b> | 1000                         |
| lb.                   | 1365   |             |      | 1500 | 1630 | <b>1765(C)</b>               | 1875 | 1995                        | <b>2150(D)</b>               | 2220 | 2330                        | <b>2470(E)</b>               |
| SINGLE                | kg.    |             | 700  | 745  | 795  | <b>880(C)<sub>103</sub></b>  | 930  | 970                         | <b>1060(D)<sub>110</sub></b> | 1100 | 1140                        | <b>1215(E)<sub>115</sub></b> |
|                       | lb.    |             | 1500 | 1650 | 1790 | <b>1940(C)</b>               | 2060 | 2190                        | <b>2335(D)</b>               | 2440 | 2560                        | <b>2680(E)</b>               |
| LT245/75R16           | DUAL   | kg.         | 720  | 765  | 820  | <b>910(C)<sub>104</sub></b>  | 960  | 1000                        | <b>1080(D)<sub>111</sub></b> | 1135 | 1170                        | <b>1260(E)<sub>116</sub></b> |
|                       |        | lb.         | 1545 | 1695 | 1845 | <b>2006(C)</b>               | 2125 | 2255                        | <b>2381(D)</b>               | 2515 | 2640                        | <b>2778(E)</b>               |
|                       | SINGLE | kg.         | 790  | 840  | 900  | <b>1000(C)<sub>108</sub></b> | 1055 | 1100                        | <b>1190(D)<sub>114</sub></b> | 1250 | 1290                        | <b>1380(E)<sub>120</sub></b> |
|                       |        | lb.         | 1700 | 1865 | 2030 | <b>2205(C)</b>               | 2335 | 2480                        | <b>2623(D)</b>               | 2765 | 2900                        | <b>3042(E)</b>               |
| LT265/75R16           | DUAL   | kg.         | 810  | 860  | 920  | <b>1030(C)<sub>109</sub></b> | 1080 | 1130                        | <b>1250(D)<sub>116</sub></b> | 1275 | 1310                        | <b>1400(E)<sub>120</sub></b> |
|                       |        | lb.         | 1740 | 1910 | 2075 | <b>2270(C)</b>               | 2390 | 2540                        | <b>2755(D)</b>               | 2825 | 2965                        | <b>3085(E)</b>               |
|                       | SINGLE | kg.         | 890  | 950  | 1010 | <b>1120(C)<sub>112</sub></b> | 1185 | 1240                        | <b>1360(D)<sub>119</sub></b> | 1400 | 1440                        | <b>1550(E)<sub>123</sub></b> |
|                       |        | lb.         | 1910 | 2100 | 2280 | <b>2470(C)</b>               | 2625 | 2790                        | <b>3000(D)</b>               | 3105 | 3260                        | <b>3415(E)</b>               |
| LT225/75R17           | DUAL   | kg.         | 665  | 710  | 750  | <b>850(C)<sub>102</sub></b>  | 885  | 920                         | <b>1000(D)<sub>108</sub></b> | 1050 | 1070                        | <b>1150(E)<sub>113</sub></b> |
|                       |        | lb.         | 1425 | 1565 | 1695 | <b>1875(C)</b>               | 1950 | 2075                        | <b>2205(D)</b>               | 2310 | 2430                        | <b>2535(E)</b>               |
|                       | SINGLE | kg.         | 730  | 780  | 825  | <b>925(C)<sub>105</sub></b>  | 970  | 1010                        | <b>1090(D)<sub>111</sub></b> | 1155 | 1180                        | <b>1250(E)<sub>116</sub></b> |
|                       |        | lb.         | 1565 | 1720 | 1865 | <b>2040(C)</b>               | 2145 | 2280                        | <b>2405(D)</b>               | 2540 | 2670                        | <b>2755(E)</b>               |
| LT245/75R17           | DUAL   | kg.         | 750  | 805  | 850  | <b>925(C)<sub>105</sub></b>  | 1005 | 1040                        | <b>1150(C)<sub>113</sub></b> | 1190 | 1220                        | <b>1320(E)<sub>118</sub></b> |
|                       |        | lb.         | 1610 | 1770 | 1920 | <b>2040(C)</b>               | 2210 | 2350                        | <b>2535(C)</b>               | 2615 | 2750                        | <b>2910(E)</b>               |
|                       | SINGLE | kg.         | 825  | 880  | 935  | <b>1030(C)<sub>109</sub></b> | 1100 | 1140                        | <b>1250(D)<sub>116</sub></b> | 1305 | 1340                        | <b>1450(E)<sub>121</sub></b> |
|                       |        | lb.         | 1770 | 1945 | 2110 | <b>2270(C)</b>               | 2430 | 2580                        | <b>2755(D)</b>               | 2875 | 3020                        | <b>3195(E)</b>               |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.



# Commercial Light Truck Radials

Light Truck **METRIC** Radial Ply Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service

| TIRES MOUNTED ON 5° DROP CENTER RIMS |        |  |      |      |      |                               |      |      |                               |      |      |                               |
|--------------------------------------|--------|--|------|------|------|-------------------------------|------|------|-------------------------------|------|------|-------------------------------|
| TIRE SIZE DESIGNATION                | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures |      |      |      |                               |      |      |                               |      |      |                               |
|                                      |        | kPa  | 250  | 280  | 310  | 350                           | 380  | 410  | 450                           | 480  | 520  | 550                           |
|                                      |        | psi  | 35   | 40   | 45   | 50                            | 55   | 60   | 65                            | 70   | 75   | 80                            |
| LT235/80R17                          | DUAL   | kg.  | 730  | 800  | 830  | 925                           | 1015 | 1010 | 1120                          | 1090 | 1180 | <b>1285(E)</b> <sub>117</sub> |
|                                      |        | lb.  | 1570 | 1725 | 1870 | 2040                          | 2190 | 2315 | 2470                          | 2560 | 2685 | <b>2835(E)</b> <sub>117</sub> |
|                                      | SINGLE | kg.  | 800  | 880  | 910  | 1030                          | 1115 | 1110 | 1215                          | 1305 | 1300 | <b>1400(E)</b> <sub>120</sub> |
|                                      |        | lb.  | 1725 | 1895 | 2055 | 2270                          | 2405 | 2545 | 2680                          | 2815 | 2950 | <b>3085(E)</b> <sub>120</sub> |
| LT215/85R16                          | DUAL   | kg.  | 630  | 690  | 720  | <b>800(C)</b> <sub>100</sub>  | 865  | 870  | <b>975(D)</b> <sub>107</sub>  | 1025 | 1030 | <b>1120(E)</b> <sub>112</sub> |
|                                      |        | lb.  | 1360 | 1490 | 1625 | <b>1765(C)</b>                | 1865 | 1985 | <b>2150(D)</b>                | 2210 | 2320 | <b>2470(E)</b>                |
|                                      | SINGLE | kg.  | 695  | 760  | 790  | <b>880(C)</b> <sub>103</sub>  | 950  | 965  | <b>1060(D)</b> <sub>110</sub> | 1130 | 1130 | <b>1215(E)</b> <sub>115</sub> |
|                                      |        | lb.  | 1495 | 1640 | 1785 | <b>1940(C)</b>                | 2050 | 2180 | <b>2335(D)</b>                | 2430 | 2550 | <b>2680(E)</b>                |
| LT235/85R16                          | DUAL   | kg.  | 720  | 790  | 820  | <b>910(C)</b> <sub>104</sub>  | 985  | 1000 | <b>1080(D)</b> <sub>111</sub> | 1165 | 1170 | <b>1260(E)</b> <sub>116</sub> |
|                                      |        | lb.  | 1545 | 1700 | 1845 | <b>2006(C)</b>                | 2125 | 2260 | <b>2381(D)</b>                | 2515 | 2645 | <b>2778(E)</b>                |
|                                      | SINGLE | kg.  | 790  | 965  | 900  | <b>1000(C)</b> <sub>108</sub> | 1100 | 1155 | <b>1190(D)</b> <sub>114</sub> | 1285 | 1290 | <b>1380(E)</b> <sub>120</sub> |
|                                      |        | lb.  | 1700 | 1870 | 2030 | <b>2205(C)</b>                | 2335 | 2485 | <b>2623(D)</b>                | 2765 | 2905 | <b>3042(E)</b> <sub>120</sub> |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Commercial Light Truck Radials

Light Truck **RADIAL & BIAS Ply** Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service

## TIRES MOUNTED ON 5° DROP CENTER RIMS

| TIRE SIZE DESIGNATION  | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures |      |      |      |                             |      |      |                              |      |      |                              |
|------------------------|--------|--|------|------|------|-----------------------------|------|------|------------------------------|------|------|------------------------------|
|                        |        | RADIAL PLY   |      |      |      |                             |      |      |                              |      |      |                              |
|                        |        | kPa  | 250  | 280  | 310  | 340                         | 380  | 410  | 450                          | 480  | 520  | 550                          |
|                        |        | psi  | 35   | 40   | 45   | 50                          | 55   | 60   | 65                           | 70   | 75   | 80                           |
|                        |        | DIAGONAL (BIAS) PLY  |      |      |      |                             |      |      |                              |      |      |                              |
| kPa                    | 210    | 240  | 280  | 310  | 340  | 380                         | 410  | 450  | 480                          | 520  |      |                              |
| psi                    | 30     | 35   | 40   | 45   | 50   | 55                          | 60   | 65   | 70                           | 75   |      |                              |
| 7.00R15LT<br>7.00*15LT | DUAL   | kg.  | 540  | 595  | 645  | <b>690(C)<sub>95</sub></b>  | 735  | 780  | <b>825(D)<sub>101</sub></b>  | 850  | 890  | <b>925(E)<sub>105</sub></b>  |
|                        |        | lb.  | 1190 | 1310 | 1420 | <b>1520(C)<sub>95</sub></b> | 1620 | 1715 | <b>1820(D)<sub>101</sub></b> | 1870 | 1960 | <b>2040(E)<sub>105</sub></b> |
|                        | SINGLE | kg.  | 610  | 670  | 730  | <b>775(D)<sub>99</sub></b>  | 830  | 880  | <b>925(D)<sub>105</sub></b>  | 965  | 1005 | <b>1060(E)<sub>110</sub></b> |
|                        |        | lb.  | 1350 | 1480 | 1610 | <b>1710(C)<sub>99</sub></b> | 1830 | 1940 | <b>2040(D)<sub>105</sub></b> | 2130 | 2220 | <b>2335(E)<sub>110</sub></b> |
| 7.50R16LT<br>7.50*16LT | DUAL   | kg.  |      |      |      |                             |      |      |                              |      |      |                              |
|                        |        | lb.  |      |      |      |                             |      |      |                              |      |      |                              |
|                        | SINGLE | kg.  |      |      |      |                             |      |      |                              |      |      |                              |
|                        |        | lb.  |      |      |      |                             |      |      |                              |      |      |                              |

|                            |        | RADIAL PLY          |      |      |      |                              |      |      |                              |      |      |                              |      |      |                              |
|----------------------------|--------|---------------------|------|------|------|------------------------------|------|------|------------------------------|------|------|------------------------------|------|------|------------------------------|
|                            |        | kPa                 | 250  | 280  | 310  | 350                          | 380  | 410  | 450                          | 480  | 520  | 550                          | 590  | 620  | 660                          |
|                            |        | psi                 | 35   | 40   | 45   | 50                           | 55   | 60   | 65                           | 70   | 75   | 80                           | 85   | 90   | 95                           |
|                            |        | DIAGONAL (BIAS) PLY |      |      |      |                              |      |      |                              |      |      |                              |      |      |                              |
|                            |        | kPa                 | 210  | 250  | 280  | 310                          | 350  | 380  | 410                          | 450  | 480  | 520                          | 550  | 590  | 620                          |
| psi                        | 30     | 240                 | 40   | 45   | 50   | 55                           | 60   | 65   | 70                           | 75   | 80   | 85                           | 90   |      |                              |
| 8.00R16.5LT<br>8.00*16.5LT | DUAL   | kg.                 | 540  | 595  | 640  | <b>690(C)<sub>95</sub></b>   | 735  | 775  | <b>825(D)<sub>101</sub></b>  | 855  | 895  | <b>925(E)<sub>105</sub></b>  | 965  | 1000 | <b>1030(F)<sub>109</sub></b> |
|                            |        | lb.                 | 1195 | 1310 | 1415 | <b>1520(C)<sub>95</sub></b>  | 1620 | 1710 | <b>1820(D)<sub>101</sub></b> | 1885 | 1970 | <b>2040(E)<sub>105</sub></b> | 2130 | 2200 | <b>2270(F)<sub>109</sub></b> |
|                            | SINGLE | kg.                 | 615  | 675  | 730  | <b>800(C)<sub>100</sub></b>  | 835  | 880  | <b>925(D)<sub>105</sub></b>  | 975  | 1020 | <b>1060(E)<sub>110</sub></b> | 1100 | 1130 | <b>1180(F)<sub>114</sub></b> |
|                            |        | lb.                 | 1360 | 1490 | 1610 | <b>1765(C)<sub>100</sub></b> | 1840 | 1945 | <b>2040(D)<sub>105</sub></b> | 2145 | 2240 | <b>2335(E)<sub>110</sub></b> | 2420 | 2500 | <b>2600(F)<sub>114</sub></b> |
| 8.75R16.5LT<br>8.75*16.5LT | DUAL   | kg.                 | 625  | 685  | 740  | <b>800(C)<sub>100</sub></b>  | 840  | 895  | <b>950(D)<sub>105</sub></b>  | 985  | 1030 | <b>1090(E)<sub>111</sub></b> | 1110 | 1150 | <b>1215(F)<sub>115</sub></b> |
|                            |        | lb.                 | 1380 | 1515 | 1630 | <b>1765(C)<sub>100</sub></b> | 1855 | 1970 | <b>2095(D)<sub>105</sub></b> | 2175 | 2260 | <b>2405(E)<sub>111</sub></b> | 2450 | 2540 | <b>2680(F)<sub>115</sub></b> |
|                            | SINGLE | kg.                 | 710  | 780  | 840  | <b>900(C)<sub>104</sub></b>  | 955  | 1020 | <b>1090(D)<sub>111</sub></b> | 1120 | 1170 | <b>1215(E)<sub>115</sub></b> | 1260 | 1310 | <b>1360(F)<sub>119</sub></b> |
|                            |        | lb.                 | 1570 | 1720 | 1850 | <b>1985(C)<sub>104</sub></b> | 2110 | 2240 | <b>2405(D)<sub>111</sub></b> | 2470 | 2570 | <b>2680(E)<sub>115</sub></b> | 2780 | 2880 | <b>3000(F)<sub>119</sub></b> |
| 9.50R16.5LT<br>9.50*16.5LT | DUAL   | kg.                 | 740  | 810  | 875  | <b>950(C)<sub>106</sub></b>  | 1000 | 1060 | <b>1120(D)<sub>112</sub></b> | 1170 | 1220 | <b>1285(E)<sub>117</sub></b> |      |      |                              |
|                            |        | lb.                 | 1635 | 1785 | 1925 | <b>2095(C)<sub>106</sub></b> | 2200 | 2330 | <b>2470(D)<sub>112</sub></b> | 2570 | 2685 | <b>2835(E)<sub>117</sub></b> |      |      |                              |
|                            | SINGLE | kg.                 | 845  | 920  | 995  | <b>1090(C)<sub>111</sub></b> | 1130 | 1200 | <b>1285(D)<sub>117</sub></b> | 1320 | 1380 | <b>1450(E)<sub>121</sub></b> |      |      |                              |
|                            |        | lb.                 | 1860 | 2030 | 2190 | <b>2405(C)<sub>111</sub></b> | 2500 | 2650 | <b>2835(D)<sub>117</sub></b> | 2920 | 3050 | <b>3195(E)<sub>121</sub></b> |      |      |                              |

NOTES: Letters in parentheses ( ) denote Load Range for which boldface loads are MAXIMUM.

International Load Index numbers are shown after the Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Commercial Light Truck Radials

Light Truck Radial Ply Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service

## TIRES MOUNTED ON FLAT BASE RIMS

| TIRE SIZE DESIGNATION | USAGE  | Tire Load Limits (kg./lb.) at various Cold Inflation Pressures |      |                               |      |      |                               |      |      |                               |                               |
|-----------------------|--------|--|------|-------------------------------|------|------|-------------------------------|------|------|-------------------------------|-------------------------------|
|                       |        | kPa  | 410  | 450                           | 480  | 520  | 550                           | 590  | 620  | 660                           | 690                           |
|                       |        | psi  | 60   | 65                            | 70   | 75   | 80                            | 85   | 90   | 95                            | 100                           |
| 7.50R16LT             | DUAL   | kg.  | 925  | <b>975(D)</b> <sub>107</sub>  | 1020 | 1065 | <b>1120(E)</b> <sub>112</sub> | 1150 | 1190 | <b>1250(F)</b> <sub>116</sub> | <b>1450(G)</b> <sub>121</sub> |
|                       |        | lb.  | 2040 | <b>2150(D)</b>                | 2245 | 2345 | <b>2470(E)</b>                | 2540 | 2630 | <b>2755(F)</b>                | <b>3195(G)</b>                |
|                       | SINGLE | kg.  | 1050 | <b>1120(D)</b> <sub>112</sub> | 1160 | 1210 | <b>1250(E)</b> <sub>116</sub> | 1310 | 1360 | <b>1400(F)</b> <sub>120</sub> | <b>1510(G)</b> <sub>122</sub> |
|                       |        | lb.  | 2310 | <b>2470(D)</b>                | 2560 | 2670 | <b>2755(E)</b>                | 2885 | 2900 | <b>3085(F)</b>                | <b>3330(G)</b>                |

|        |      | kPa                              | 500  | 550  | 900                           |
|--------|------|----------------------------------|------|------|-------------------------------|
|        |      | psi                              | 75   | 80   | 85                            |
|        |      | 8R17.5LT<br><b>M773 SWP Only</b> | DUAL | kg.  | 1125                          |
| lb.    | 2480 |                                  |      | 2625 | <b>2755(E)</b>                |
| SINGLE | kg.  |                                  | 1155 | 1220 | <b>1285(E)</b> <sub>116</sub> |
|        | lb.  |                                  | 2545 | 2690 | <b>2835(E)</b>                |

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

**IMPORTANT — Always use approved tire and rim combinations for diameter and contours.**