



16" & 17"

BRIDGESTONE
Firestone

TIRE SIZE
LT215/85R16
LT225/75R16
LT245/75R16
LT245/70R17
LT235/85R16
LT265/75R16
195/75R16*
235/65R16*
*FS Transforce CV only

bandag

TIRE SIZE
LT215/85R16
LT225/75R16
LT245/75R16
LT245/70R17

Transforce AT2
(Steer or Drive)



Transforce HT2
(Steer or Drive)



FS Transforce CV*
(Steer or Drive)



R238
(Steer or Drive)



MetroMax™ Rib
(Steer or Drive)



BDLT
(Drive)



BACKUP

BDR-AS™
(Drive)



19.5"

BRIDGESTONE

bandag

TIRE SIZE
225/70R19.5
245/70R19.5

R238
(Steer or Drive)



M729F
(Drive)



UAP2 FuelTech™
(Steer)



BDR-HG & -HGL
(Drive)



BDR-AS™
(Drive)



BACKUP

BDLT
(Drive)



For commercial tires 19.5" or larger a ply rating of 14 or higher is recommended.



22.5" & 24.5"

BRIDGESTONE

bandag

TIRE SIZE
295/75R22.5*
11R22.5*
11R24.5
285/75R24.5

R213
(Steer)



R2835 ECOPIA
(Steer)



R268 ECOPIA
(Steer & Drive)



M726ELA
(Drive)



M760 ECOPIA
(Drive)



M771*
(Drive)



B760 FuelTech™
(Drive)



HT5 FuelTech™
(Drive)



MegaTrek™
(Drive)



R268 ECOPIA
(Steer & Drive)



BDR-HG
(Drive)



BDR-AS™
(Drive)



Ultra Drive
(Drive)



R250ED**
(All Position)



For commercial tires 19.5" or larger a ply rating of 14 or higher is recommended.

SPECS

TIRE SPECS

POSITION	FLEET RETREADS?	PULL POINT	PSI	MATCHING
Steer	No	4/32nds	Reference fleet usage BASys profile	
Drive	Yes	2/32nds		4/32nds

DUAL MATCHING INSTRUCTIONS

- Follow industry best practices on dual & axle tread depths.

TIRE MOUNTING

- Follow all applicable OSHA and RMA safety procedures.
- Proper mounting procedures must be followed or sudden tire failure, personal injury, and/or death may result.
- Use only double seal flow through valve caps
- Always use personal protective equipment (PPE) INCLUDING Eye Safety Protection, Gloves, Back Supporter, etc. Safe work practices must always be followed. Refer to the TMC Recommended Practice Manual for additional information.

RETREADS

- All casings should be inspected by a Bandag or Dealer representative
- Ozone/weather checking must be acceptable as defined by supplied ozone template
- Reference the BASys profile under Fleet Usage for more details

REMOVAL

- Clearly identify nail holes and damage in removed tires by circling with tire chalk

SERVICES AND LABOR

- For specific requirements, refer to current service level agreements

WARRANTIES

- All warranty claims will follow the Bandag Retread national warranty guidelines.
- All warranty claims will follow the Bridgestone Truck and Bus national warranty guidelines

EMERGENCY ROAD SERVICES

- Contact Bridgestone Emergency Road Services at 1-844-85-TIRES or go to <https://commercial.bridgestone.com/en-us/find-dealer>

SCRAP HANDLING

- All Scrap Tires must be rendered unusable.
- All out-of-spec tires will be disposed of in a lawful manner.

CASING BRANDS ACCEPTED

- | | | |
|---------------|---------------|-------------|
| • Bridgestone | • Continental | • Firestone |
| • General | • Michelin | • Goodyear |
| • Hankook | • Toyo | • Yokohama |
| • Kelly | • Goodrich | |

TEAM INFORMATION

FLEET TEAM

Fleet Usage Solutions -

CUSTOMER NAME

Contact Name

LOCATION

DEALER TEAM

SERVICE PROVIDER NAME

Contact Name

LOCATION

EMAIL

Phone Number